



AIRE Quick Protector Berm

P/N 914-040612 4'x6'x12"

- Spill containment system has quick set up, collapsible side walls provide drive in/drive out capability from any direction
- The inside stays are as easy as lifting the wall and lock into place by themselves which ensures a 24/7 protection
- Inner-wall stay are fastened by berm wall strips, so no loose parts
- Can be placed flush against walls
- Inner dimensions will diminish in a minimal amount depending on height of berm wall
- Fully thermal welded 1.5" seams
- Easy, all-in-one design. No tools require
- Spill berm easily folds up into a small package, allowing easy transportation
- Berm is constructed of 30 oz chemically resistant material and is designed for heavy UV exposure
- Berms comes with easy to use ground stakes for high wind environments as needed
- Spill containment berms are designed for use with any item containing an environmental ground hazards. Ie: fuel tanks, totes, fabric pillow tanks, blivets, drum pallets, fracking operations, wheeled equipment and much more
- Great for long term placement
- EPA, OSHA, NPDES compliant. Meets 40 CFR 112.7, 40 CFR 122.26, 40 CFR 264.175
- Includes basic repair kit
- Standard 1 year warranty
- Proudly Made in the USA
- See website for video of set up
- Custom sizes, colors, and designs available. Call 1.800.247.3846
- Accessories available include – Bazooka Drain System, Ground Pad, Track Mats, and Drain Valve

Internal Width	4	ft.
Internal Length	6	ft.
Wall Height	12	in
Weight	26	lbs.
Sump	179	gal.
Containment Area	24	sq. ft.
Set Up Dimension	4x6	ft.
Stake Down Points	4	ea.
Material ASTM D751	30	oz.
Low Temp. ASTM D2136	-30	F
High Temp. ASTM D471	212	F
Puncture ASTM D4833	250	lbf
UNSPSC	24111812	

